

DYNAMOMETER AND DIAGNOSTIC TEST EQUIPMENT

FEATURED DYNAMOMETER OF:







Dynojet Research, Inc. 2191 Mendenhall Drive North Las Vegas, NV 89081 Tel (800) 992-3525 Int Tel (702) 673-4010 Fax (702) 633-4821

www.dynojet.com



#### **MODEL 2001 / 2501 MOTORCYCLE CHASSIS DYNAMOMETER**

# ABOVE GROUND MODEL STANDARD FEATURES AND EQUIPMENT

- Measures up to 750hp and 200mph
- Eddy Current Load Absorption Unit (250 series only)
- Powder coated chassis, wheelbase capability up to 84 inches (from rear axle to front tire)
- NEW PowerCore Software suite with WinPEP 8 (PC, monitor, printer, etc. not included)
- NEW DynoWare RT dynamometer electronics and hardware
- Integrated control panel stand with console
- Ignition wire inductive tachometer pickup leads
- Front wheel lock
- 2 Channels of Automatic Conditions Measurement (absolute pressure, air temp, humidity)

- 4 Analog Input Channels for 0-5v sensors (sensors and cables not included)
- 14 expansion ports for DynoWare RT accessories and DJ-CAN devices (such as Power Commander, Power Vision, Autotune, etc.)
- Starter system to spin roller (12V, battery not included)
- Installation and operation manuals
- One year replacement parts warranty\*\*
- Toll-free technical support

Model 200i	\$13,900. <sup>00</sup> usp
Model 250i	<b>\$20,900.</b> 00 usp

## PIT MODEL STANDARD FEATURES AND EQUIPMENT

- Measures up to 750hp and 200mph
- NEW PowerCore Software suite with WinPEP 8 (PC, monitor, printer, etc. not included)
- NEW DynoWare RT dynamometer electronics and hardware
- 2 Channels of Automatic Conditions Measurement (absolute pressure, air temp, humidity)
- 4 Analog Input Channels for 0-5v sensors (sensors and cables not included)
- 14 expansion ports for DynoWare RT accessories and DJ-CAN devices (such as Power Commander, Power Vision, Autotune, etc.)
- Integrated control panel stand with console
- Ignition wire inductive tachometer pickup leads
- Power carriage for button operated wheelbase adjustment
- Pit Covers
- Compact design allows for smaller pit size

- Front wheel lock
- Starter system to spin roller (12V, battery not included)
- Installation and operation manuals
- One year replacement parts warranty\*\*
- Toll-free technical support
- Eddy Current Load Absorption Unit (250 series only)

Model 200ip	\$13,900. <sup>00</sup> usd
Model 250ip	\$ <b>20,900.</b> 00 usp



#### MODEL 2001X / 2501X POWERSPORTS CHASSIS DYNAMOMETER

#### ABOVE GROUND MODEL STANDARD FEATURES AND EQUIPMENT

- Accommodates Motorcycles and most other powersports platforms (ATV's, Side-by-Sides, Go-Karts, and Trikes)
- Measures up to 750hp and 200mph
- Eddy Current Load Absorption Unit (250 series only)
- Powder coated chassis, wheelbase capability up to 84 inches (from rear axle to front tire)
- NEW PowerCore Software suite with WinPEP 8 (PC, monitor, printer, etc. not included)
- NEW DynoWare RT dynamometer electronics and hardware
- Integrated control panel stand with console
- Ignition wire inductive tachometer pickup leads
- Front wheel lock
- 2 Channels of Automatic Conditions Measurement (absolute pressure, air temp, humidity)

- 4 Analog Input Channels for 0-5v sensors (sensors and cables not included)
- 14 expansion ports for DynoWare RT accessories and DJ-CAN devices (such as Power Commander, Power Vision, Autotune, etc.)
- Starter system to spin roller (12V, battery not included)
- Installation and operation manuals
- One year replacement parts warranty\*\*
- Toll-free technical support

Model 200iX —	<sup>\$</sup> 19,900. <sup>00</sup> usp
Model 250iX	\$ <b>26,900.</b> 00 usp

#### PIT MODEL STANDARD FEATURES AND EQUIPMENT

- Accommodates Motorcycles and most other powersports platforms (ATV's, Side-by-Sides, Go-Karts, and Trikes)
- Measures up to 750hp and 200mph
- Eddy Current Load Absorption Unit (250 series only)
- NEW PowerCore Software suite with WinPEP 8 (PC, monitor, printer, etc. not included)
- NEW DynoWare RT dynamometer electronics and hardware
- 2 Channels of Automatic Conditions Measurement (absolute pressure, air temp, humidity)
- 4 Analog Input Channels for 0-5v sensors (sensors and cables not included)
- 14 expansion ports for DynoWare RT accessories and DJ-CAN devices (such as Power Commander, Power Vision, Autotune, etc.)
- Integrated control panel stand with console
- Ignition wire inductive tachometer pickup leads
- Power carriage for button operated wheelbase adjustment
- Compact design allows for smaller pit size

- Front wheel lock
- Automatic atmospheric conditions measurement (absolute pressure, air temp, humidity)
- Starter system to spin roller (12V, battery not included)
- Installation and operation manuals
- One year replacement parts warranty\*\*
- Toll-free technical support

Model 200ipX ————	\$19,900.00 usb
Model 250ipX ————	\$ <b>26,900.</b> 00 usd
Model 250iXW ————	\$ <b>26,900.</b> 00 usp



### **MODEL SD12 SCOOTER DYNAMOMETER**

# STANDARD FEATURES AND EQUIPMENT

- Measures up to 33.5hp and 109mph
- Minimum and Maximum wheelbase 60-74 in / 152-188 cm (Front of front tire to middle of rear tire - subtract half of front tire diameter for axle to axle wheel base)
- Powder coat finish on frame and attachments
- Folding design with rollers allows easy storage, maximizing workshop space
- Brake type Spring Applied Mechanical Band (manually foot operated)
- Power requirements: one 110-220VAC (Domestic or EU Power)
- Software and hardware to interface (PC, monitor, printer, etc. not included)

#### **SPECIFICATIONS**

- Total Length (unfolded with ramp down) 132 in / 335 cm
- Total Length (unfolded with ramp up) 99 in / 251 cm
- Total Length (folded) 21 in / 533 cm
- Total width (folded: 24 in/ 61 cm Unfolded: 34 in / 86 cm)
- Total height (folded 83 in /211cm Unfolded 24 in / 61 cm)
- Weight: 437 lb / 198.22 kg (dynamometer only)
- Max Power: 25kW (33.5hp)
- Max Torque: 45Nm (33.5lb-ft)
- Max Speed: 175 km/hr (109 mph)
- One year replacement parts warranty\*\*
- Toll-free technical support

Model SD12 -	 \$8.900.	<sup>00</sup> IISN



# DUTTO DE DYNAMOMETER AND DIAGNOSTIC TEST EQUIPMENT

ITEM	DETAIL	PRICE
Extended wheelbase carriage	Accommodates 102" wheelbase measured from rear axle to front tire	\$1,200.00 USI
AFR-2 (Dual AFR Monitor)	Measures real-time air/fuel ratios with integrated high-flow "pump" inside dyno (requires shop air)	\$1,500.00 usi
Includes professional grade Riv-Nut tool, drill bit, and enough hardware to sample up to 25 bikes! (Includes bolts, washers, Riv-Nuts, specialty bolts, and billet manifold interfaces.) Recommended to be used with Dynojet Gen4 Exhaust Gas Pump		\$347. <sup>95</sup> USD
Stealth Extraction Interface Kit (No Riv-Nut Tool)	Includes drill bit, bolts, washers, Riv-Nuts, specialty bolts, and billet manifold interfaces	\$ <b>299.</b> 95 USD
Inductive RPM Connection Kit	This harness kit aids dyno operators in establishing engine RPM signals with select motorcycles. Each harness uses OEM style connectors, plugs in-line with the stock ignition system, and the non-loomed wiring makes it easy for the Dynojet Inductive RPM to clamp onto. Works with several motorcycles: Denso coil ignitions, Ducati, KTM, Polaris, Can-Am, BMW, Aprilia and Harley-Davidson®.	\$149.ºº usp
Torque Cell Module	Measures real-time torque, and allows sweep, step and custom load simulation tests	\$1,100.00 usc
Eddy Current Load Absorption Unit	Allows load testing by close-looping on rpm, speed or percentage of load. (Included on 250i/250ix series models)	\$ <b>8,000.</b> 00 us
Dual Cooling Fan System	Integrated cooling fans with adjustable arms. 1,800 CFM each fan	\$ <b>2,500.</b> 00 us
Monitor Tray	Bolts onto the control panel arm and holds the monitor, keyboard and mouse	\$ <b>295.</b> 00 USD
Primary Folding Ramp	Gas strut assisted folding ramp bolts directly to the dynamometer	\$1,450.00 us
Secondary Folding Ramp	Supplemental ramp for "x" model dynos (both ramps required)	\$1,250.00 us
Power Wheel Clamp	Motor driven wheel clamp controlled through the control panel for securing front wheel without stepping off the motorcycle	\$1,100.ºº us
Power Carriage	Motor driven carriage controlled from control panel for adjusting wheelbase without stepping off the motorcycle	\$300.ºº usp
Air Brake	Air actuated disk brake used for slowing drum. *not necessary with 250i series dynos*	\$1,400.ºº us
Fatboy Adapter	Necessary for securing motorcycles with solid or heavily spoked front wheels *not needed with Power Wheel clamp*	\$100.00 USD
	Analog Sensor Cable Kit (Used for connecting customer supplied 0-5v sensors to DynoWare RT Main Control Module – includes 4 harness kits)	\$ <b>50.</b> 00 usp
Analog Channel Accessories	0-50psi Absolute Pressure Sensor	\$125.00 USD
	0-100psi Relative Pressure Sensor	\$1 <b>25</b> .00 USD
IR-Temp Sensor Kit	·	
O2 Sensor Kit (6ft)	Includes one wideband O2 sensor with six foot harness for use with AFR-2 for dual air/fuel readings	\$185.00 USD
O2 Sensor Kit (12ft)	Includes one wideband O2 sensor with twelve foot harness for use with AFR-2 for dual air/fuel readings	\$185.00 USD
O2 Sensor Test Gas Kit	Includes 34L gas cylinder with regulator. Used to baseline new O2 sensors, compare values with age and determine when to replace. Average test is 10-15 seconds and one bottle provides approx 68 min of test time.	\$ <b>220.</b> 00 usp
H-D Data Link	Data Link system that connects LAN and J1850 data from H-D Models with Delphi EFI to DynoWare RT	\$400.ºº usp
Power Vision Shop Tuner Kit	Includes a Power Vision, AutoTune Pro Module, and all necessary cables in order to tune J1850 or CAN models.	\$799. <sup>95</sup> USD
H-D Fuel Tap	Interface for acquiring fuel pressure readings from 2001 and newer H-D motor- cycles. Includes 0-100PSI sensor, adapters and all hardware.	\$ <b>429.</b> 00 usp
X Upgrade	Allows dyno to additionally accommodate most other powersports platforms (ATV's, Side-by-Sides, Go-Karts, and Trikes). Standard feature on "x" model powersports dynamometers.	\$ <b>7,900</b> .00 us